QUOTE REQUEST

FABRIC & LAMELLA BELLOWS

Www.hennigworldwide.com

Please complete this form and email to info@hennig-inc.com or fax to your desired location. Find your nearest Hennig location.

COMPANY (complete address)	Name
	Title
	E-mail
	Phone Fax Date/
TECHNICAL DATA	
Quantity	MATERIAL OF END FRAMES
5 Required stroke	Steel Stainless Steel
Compressed length (min)	○ Aluminum ○ PVC
Extended length (max)	
Fold height	MOUNTING OPTIONS
Width of bellows	○ Half Fold ○ Full Fold ○ External Flange ○
	○ Collar ○ Velcro
Left-hand lateral height (outside) Right-hand lateral height (outside)	MODE OF OPERATION
Height of bellows above support	○ Horizontal ○ Vertical ○ Cross-rail
Lower wrap-around	Other
Travel speedm/min	
Accelerationm/s²	CONDITIONS OF APPLICATION
Width of slideway	☐ Chips ☐ Sparks ☐
Length of lamellas	☐ Coolant ☐ Oil ☐ Dust ☐ Indoor ☐ ☐ ☐
	☐ Temperature ☐ Outdoor
Inner diameter of bellows Outside diameter of bellows	□ Other
To a confidence de la confidence	
Type or macnine	SHAPE
Number of strokes per day	Choose one —
Coolant, lubricants	-or-
Type of swarf	Use page 25 and write the corresponding letter here
Ambient temperature	letter fiere
Linear type of slideway	
Photos Available	
DWGs or Sketches Available	
División silecteres Available	